Sunkye Nanominiature Connector Product Selection Guide

	R06	R06F	R06M2	R06M3	R06M8	R06C	R06S
	P						
Applications	system interconnectio	highly reliable. This series have 3 kinds of tail	R06M2 Twist flexible micro pin (twist pin), 0.635mm pitch, micro miniature outline dimension	R06M3 Screw nut locking, it is gently when inserted and extract, stably locked	R06M8 is free mounted, not fixed, usually mated with receptacle which have nut. Recommend ed JC types of screws, tight by miniature stright screwdriver.	R06C crimp termination High reliable connectors	R06S stright to PCB which have 3 kinds of tail length, customized produce for another length
	Plug and		Plug and	Plug and	Plug and	Plug and	Plug and
Available layouts	Socket	Plug and Socket	Socket	Socket	Socket	Socket	Socket
Current Rating	1A max.	1A max.	1A max.	1A max.	1A max.	1A max.	1A max.
Contact	Twist Pin	Twist Pin	Twist Pin	Twist Pin	Twist Pin	Twist Pin	Twist Pin
Contact Resistance	21 milliohms max.	21 milliohms max.	21 milliohms max.	21 milliohms max.	21 milliohms max.	21 milliohms max.	21 milliohms max.
Shell Material	Metal	Metal	Metal	Metal	Metal	Metal	Metal
Available layouts of contacts	9,15,21,25,31 ,37,51,65&69	9,15,21,25,31,37, 51,65&69	9,15,21,25,31 ,37,51,65&69	9,15,21,25,31 ,37,51,65&69	9,15,21,25,31 ,37,51,65&69	9,15,21,25,31 ,37,51,65&69	9,15,21,25,31 ,37,51,65&69
Terminal Mounting	Crimping Solder Cup PCB Right angel 91°to PCB	Right Angle to PCB	Vertical SMT	Horizontal SMT	Straddle Flexible SMT	Crimping Solder Cup PCB Right angel 90°to PCB	Stright to PCB
RoHS	A	A	A 141 1	A	A	A	A
Plating	Availble	Availble	Availble	Availble	Availble	Availble	Availble
Factory Terminated	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Space Application	Yes	Yes	Yes	Yes	Yes	Yes	Yes